

## AXIAL THERMOCONVECTORS



# TS-A




### PROFILE

The TS-A series AXIAL THERMOCONVECTORS are characterized by the employ of different by the use of different fin geometries, different forms, materials and innovative design. This is an innovative product that can fully satisfy the needs of operators in the industrial cooling. The combination of three factors such as geometry wings (different tube diameters and special fins), proper fans and different modules allows in an optimal way to combine the following aspects:

- maximum capacity in relation to the size of the heat exchanger;
- loss of load of the primary fluid optimized through the use of different pipe diameters;
- opportunity for optimal choice of the equipment through the use of modules of different length;
- compliance with the strictest environmental standards in terms of noise pollution.

### FANS

This will involve the use of fans in numbers varying from 1 to 6, in single and double cylinder bank, to develop power from 50 kW to 200 kW at nominal standard conditions. The fairing is made of galvanized steel, powder painted with polyurethane resin to ensure maximum strength and solidity of the unit. Fans are used for outdoor uses, 400V/3Ph/50Hz double speed to get up to 8 sound levels equal diameter.



### ACCESSORIES

Is available on demand, a complete set of accessories including: cut phase speed reducer and inverter; fins of different materials (aluminium, copper, aluminium coil coating and double pass), copper tubes and stainless steel, special motors to different voltages and high temperature.



